

CERTIFICATE OF COMPLIANCE

Certificate Number 20160218-R38491
Report Reference R38491-20151130
Issue Date 2016-FEBRUARY-18

Issued to: GUANGDONG BE-TECH SECURITY SYSTEMS LIMITED
No. 17, Keyuan 3 Road, Ronggui, Shunde High-Tech Zone
Foshan
Guangdong 528306 CHINA

This is to certify that representative samples of ELECTRICALLY CONTROLLED SINGLE-POINT LOCKS AND LATCHES

See next page for Models

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Fire Tests of Door Assemblies," ANSI/UL10B
Positive Pressure Fire Tests of Door Assemblies,"
ANSI/UL10C
Standard Method for Fire Tests of Door Assemblies,"
CAN/ULC-S104-10

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number 20160218-R38491
Report Reference R38491-20151130
Issue Date 2016-FEBRUARY-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

PRODUCT COVERED:

USL/CNL Electrically controlled single point lock and latches.
Mortise type, "Base RFID, 20 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Base RFID, 65 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Base RFID, 75 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Base RFID, 81 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Guardian RFID, G0 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Guardian RFID, G1 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Guardian RFID, G2 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Guardian RFID, G3 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Guardian RFID, G4 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.
Mortise type, "Shadow RFID, S2 Series, Euro(S65) and ANSI(S51) Lockcase", battery operated unit, with (15.9mm and 18.2mm) Latch bolts.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

